

**FLOOD PHOTOMETRIC REPORT**



CATALOG: I1341



MANUFACTURER: PRO-LIGHT  
TEST DATE: 2012-06-21  
DESCRIPTION: I1341  
LAMP: I1341-9W-3000K-38  
LAMP OUTPUT: 1 LAMP, RATED LUMENS/LAMP: 1066.9  
INPUT WATTAGE: 8.1  
LUMINOUS OPENING: POINT  
NEMA TYPE: 4 X 5  
MAX CD: 693.4 AT HORIZONTAL: -2°, VERTICAL: 0°  
EFFICIENCY: 35.1%



No  
Photo  
Available

SEE REPORT NOTES \*\*



\*\*FILE DOES NOT INCLUDE SUFFICIENT VERTICAL DATA TO PROPERLY CALCULATE BUG AND LCS UPLIGHT.  
\*\*FILE DOES NOT INCLUDE UPPER HEMISPHERE DATA(90-180) AND HAS CD > 0 AT 90° VERTICAL.

VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2017, ACUITY BRANDS LIGHTING.  
THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.



**ZONAL LUMEN SUMMARY**

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	260.3	24.4%	69.5%
0-40	310.7	29.1%	82.9%
0-60	362.1	33.9%	96.7%
60-90	12.4	1.2%	3.3%
0-90	374.6	35.1%	100%


**LUMENS PER ZONE**

ZONE	LUMENS	% TOTAL
0-10	56.7	15.1%
10-20	114.5	30.6%
20-30	89.0	23.8%
30-40	50.4	13.5%
40-50	31.5	8.4%
50-60	20.0	5.3%
60-70	9.9	2.6%
70-80	2.4	0.6%
80-90	0.1	0.0%

**FLOOD SUMMARY**

	EFFICIENCY	LUMENS	HORIZONTAL SPREAD	VERTICAL SPREAD
FIELD (10%):	27.9%	297.4	69.7	72.8
BEAM (50%):	15%	160.0	35	36.3
TOTAL:	35.1%	374.2		

**LCS Graph**



**Back Light**

**Forward Light**

Scale = Max LCS %

Trapped Light: 692lm, 64.9%

**CANDELA TABLE - TYPE B**

	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	
90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
70	0	0	0	0	1	1	2	3	3	3	3	3	3	2	1	1	0	0	0	0
60	0	0	0	1	1	2	4	7	8	9	9	7	5	2	1	1	0	0	0	0
50	0	0	1	2	7	11	15	18	21	21	20	18	14	10	6	2	1	0	0	0
40	0	0	1	5	12	19	26	33	38	40	37	31	24	18	11	4	1	0	0	0
30	0	0	2	9	18	28	38	50	61	65	58	46	35	25	17	8	1	0	0	0
20	0	1	3	13	23	37	60	101	162	192	146	87	51	33	21	10	2	0	0	0
10	0	1	4	15	27	45	85	184	341	401	309	150	70	39	24	13	2	0	0	0
0	0	1	4	16	30	52	112	300	598	691	547	234	91	45	27	14	2	0	0	0
-10	0	1	4	16	30	51	109	286	571	662	505	212	87	44	26	13	2	0	0	0
-20	0	1	4	15	28	47	92	221	426	493	371	165	76	41	24	12	2	0	0	0
-30	0	1	3	13	24	38	60	105	162	184	145	93	56	35	21	11	2	0	0	0
-40	0	0	2	10	19	29	42	63	88	97	82	59	40	26	16	7	1	0	0	0
-50	0	0	1	6	13	21	27	35	41	43	40	34	26	18	11	4	1	0	0	0
-60	0	0	1	2	6	12	16	19	22	22	21	18	15	11	5	1	1	0	0	0
-70	0	0	0	1	3	5	7	8	10	10	9	8	6	4	2	1	0	0	0	0
-80	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0