

**FLOOD PHOTOMETRIC REPORT**



CATALOG: I1360



MANUFACTURER: PRO-LIGHT  
TEST DATE: 2014-06-14  
DESCRIPTION: I1360  
LAMP: I1360-30W-40D-4000K  
LAMP OUTPUT: 1 LAMP, RATED LUMENS/LAMP: 2248.3  
INPUT WATTAGE: 28.5  
LUMINOUS OPENING: POINT  
NEMA TYPE: 5 X 5  
MAX CD: 3,903.5 AT HORIZONTAL: -2°, VERTICAL: 0°  
EFFICIENCY: 99.9%



No  
Photo  
Available

SEE REPORT NOTES \*\*



\*\*FILE DOES NOT INCLUDE SUFFICIENT VERTICAL DATA TO PROPERLY CALCULATE BUG AND LCS UPLIGHT.  
\*\*FILE DOES NOT INCLUDE UPPER HEMISPHERE DATA(90-180) AND HAS CD > 0 AT 90° VERTICAL.

VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2017, ACUITY BRANDS LIGHTING.  
THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.



**ZONAL LUMEN SUMMARY**

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	1,653.0	73.5%	73.5%
0-40	2,058.6	91.6%	91.6%
0-60	2,229.0	99.1%	99.1%
60-90	19.2	0.9%	0.9%
0-90	2,248.2	100%	100%


**LUMENS PER ZONE**

ZONE	LUMENS	% TOTAL
0-10	323.1	14.4%
10-20	699.6	31.1%
20-30	630.3	28.0%
30-40	405.6	18.0%
40-50	138.9	6.2%
50-60	31.5	1.4%
60-70	14.5	0.6%
70-80	4.3	0.2%
80-90	0.4	0.0%

**FLOOD SUMMARY**

	EFFICIENCY	LUMENS	HORIZONTAL SPREAD	VERTICAL SPREAD
FIELD (10%):	91.8%	2,064.7	80.2	79
BEAM (50%):	44.6%	1,003.0	40.1	42
TOTAL:	99.9%	2,246.0		

**LCS Graph**



**Back Light**

**Forward Light**

Scale = Max LCS %

Trapped Light: 0lm, 0%

**CANDELA TABLE - TYPE B**

	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	
90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
70	0	1	1	2	3	5	7	8	8	8	8	8	7	5	2	1	1	1	1	0
60	0	1	1	2	6	13	17	19	20	20	20	19	17	11	5	2	1	1	1	0
50	0	1	2	8	14	22	36	48	74	88	61	45	29	18	13	5	2	1	0	0
40	0	1	3	13	22	41	163	285	351	384	326	232	107	31	18	10	2	1	0	0
30	0	1	5	17	28	70	400	730	852	909	814	581	250	48	22	15	3	1	0	0
20	0	1	7	19	43	279	698	1251	1934	2131	1698	973	561	123	28	16	4	1	0	0
10	0	1	9	21	53	425	905	1752	2825	3117	2453	1344	753	203	34	17	4	1	0	0
0	0	1	10	22	58	509	1020	2232	3523	3868	3078	1693	827	287	38	18	5	1	0	0
-10	0	1	9	21	52	405	891	1709	2721	2997	2377	1314	739	194	33	17	4	1	0	0
-20	0	1	7	20	41	255	670	1200	1824	1995	1616	948	535	113	28	16	4	1	0	0
-30	0	1	5	17	27	58	355	708	834	861	795	594	214	43	22	15	3	1	0	0
-40	0	1	3	13	21	36	143	269	324	344	304	228	91	28	18	10	2	1	0	0
-50	0	1	2	8	14	21	30	39	53	63	46	36	24	18	12	6	2	1	0	0
-60	0	1	2	3	6	13	16	18	19	19	19	17	16	12	5	3	2	1	0	0
-70	1	1	2	2	3	6	7	8	9	9	8	8	7	6	3	2	2	1	1	0
-80	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0