www.proximadriver.it

Data sheet

DG Tecnologie - Via S. D'Acquisto, 42/F PONTEDERA (PI)

Serie LNT

Features

- Universal Input: 200-240VAC 50Hz
- RoHS Compliance
- EMI Standard EN55015:2019+A11
- Safety Standard: EN61347-1:2015, EN61347-2- 13:2014+A1:2017, UL8750
- Inrush current<65A AC230V/50Hz
- High efficiency & low power consumption
- Short Circuit, Over Current and Over Voltage Protection
- Over temperature protection
- 100% full load burn-in test
- Super slim design

Applications:
LED lights bring
LED indoor lighting
LED decorative lighting

Input Voltage	220-240VAC
Voltage Tolerance	± 5%
Operating temperature	-20°C +50°C
Over Load	Hiccup mode, recovers automatically after fault condition is removed
Over Voltage	Protection type: Shut down o/p voltage, re-power on to recover
Over Temperature	Shut down o/p voltage, re-power on to recover
Safety Regulations	EN61347-2-13:2014+A1:2017,EN61347-1:2015;EN62493:2015
Harmonic	EN61000-3-2 Class C EN61000-3-3
EMI	Compliance EN55015
EMS	Compliance 61547:2009

Model	Power	DC Output	Rated Current	Efficency	Size	Packaging	Weight
LNT-75-24	75W	24V	3125mA	88%	305 x 30 x 17mm	100 pcs / carton	0,230
LNT-100-24	100W	24V	4160mA	92%	305 x 30 x 17mm	50 pcs / carton	0,160

DG Tecnologie non fornisce alcuna rappresentazione o garanzia relativamente all'accuratezza o alla completezza delle informazioni incluse e non può essere ritenuta responsabile di eventuali azioni basate su di esse. Le informazioni riportate nel presente documento non hanno alcuno scopo commerciale e non fanno parte di alcun preventivo o contratto, salvo diversamente concordato con DG Tecnologie.
Pro-Light è un marchio registrato di DG Tecnologie s.r.l. Via Salvo D'Acquisto, 42/F - 56025 Pontedera Pisa
Prodotto fabbricato in Cina, importato da DG Tecnologie s.r.l.

Aggiornato al 24 nov 2022 13:4